

Motorcycle Key	Tires – Condition *
Helmet	Brake Pads – Worn?
Leathers	Brake Fluid – DO NOT OVERFILL **
Boots	Chain – Adjust and Lube
Gloves	Sprocket Condition – Worn?
Back protector – recommended	Valve Caps
Gas Can	Wheel Weights - Taped
Tools & Tire Pressure Gauge	Axels – Correct Torque / Cotter Pin
Duct Tape / Zip Ties	Fork Seals – Leaking?
Lubricants / Spray Polish	Oil Level / Cap & Filter – Tight? ***
Rags / Paper Towels	Levers Adjusted
Canopy / Chairs	Throttle Play – Snaps closed
Sunglasses / Hat	Body Work – Securely Fastened
Sunscreen / Lip Balm	Tail Light – Taped or Disconnected
Cooler / Fluids and Snacks	Mirrors - Taped or Removed

- * Air pressure is VERY IMPORTANT. Our track tire vendor will have a sign board with all tire brands and recommended track pressures.
- ** DO NOT OVERFILL brake fluid reservoirs past the full mark. Overfilling can cause the brakes to lock up when hot.
- *** When changing the oil filter, make sure to remove the old O Ring from the mating surface. Double O Rings WILL FAIL resulting in major oil loss.